



Description

Gripset DM is a premium grade cementitious mortar compound designed for use in conjunction with other Gripset membranes and additives. Gripset DM is compatible with Gripset 51; Gripset 11Y and Gripset GP (refer to relevant product information sheets for further information) for superior high performance render finishes



Features & Benefits

- * Easily dispersed with Gripset products.
- * Time saving pre-mixed additive ready for direct use.
- * Provides a quality surface finish
- * Compatible with tile adhesives, renders, screeds and other wall/floor coatings

Application

Gripset DM is a versatile dry cementitious additive designed for direct use with a number of Gripset products for waterproofing or repair applications. As each application for the use of Gripset DM differs, refer to individual data sheets of Gripset products for specific details. Applications include:

Uses

- * Patch repairs
- * Thin build renders, bagging coats, general filling of voids
- * Waterproof screeds and feather edge coatings
- * Fillets
- * Waterproof slurries/primers
- * Levelling and mortar repairs

Storage

- * Best stored at room temperature in a dry area.
- * Avoid cold freezing conditions and off concrete floors.
- * Shelf life is 6 months when stored in a dry place.

Packaging

- * 20kg bags

Precautions

- * Gripset DM consists of cement products which may contain crystalline silica, therefore when using this product precaution must be taken to prevent long term exposure to dust.
- * Safety Data sheet (SDS) available.
- * For further information about this product contact technical department of Gripset Industries.

Clean up

- * With soapy water while in a dry or wet state.
- * Once dried product needs to be removed mechanically.

Notes

It is recommended before commencing the application; that adhesion of products to be used (e.g. primers, membranes, coatings adhesives etc) is tested over a typical area of the prepared surface to ensure satisfactory adhesion. It is the responsibility of the applicator to carry this out and accept the substrate suitability before any application starts. Gripset Industries offers a service for pre testing adhesion to surfaces for large commercial areas or unusual substrates. For further details contact Gripset Industries. Details contained in product data sheets are general. For any situation or items not covered in this data sheet, it is the responsibility of the applicator to check with Gripset Technical Services before commencing the application. A written confirmation will then be issued by Gripset Technical Services.

Gripset Industries Pty Ltd

ABN: 64 137 930 093

Telephone: +61 (8) 8124-7300 or 1800 650 435

Email: techenquiries@gripset.com

Website: www.gripset.com

Product Disclaimer

This Product Data Sheet (PDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this PDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Gripset Industries does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether or not in accordance with any advice, specification, recommendation or information given by it.