

SUBSTRATE READINESS CHECKSHEET

for WPS Liquid Membranes/duroTUF TPO Membrane

Schluter 25 Uncoupling System

Project/Site Name	
Site Address	
Applicator	
Main Contractor	

QC process	✓ Tick when completed
The specified Liquid membrane/duroTUF TPO membrane is installed correctly and has been QC managed and signed off. For Acoustic System installation, use duroTUF TPO Fleece back membrane.	<input type="checkbox"/>
The substrate surface is clean, free from debris, contaminants and smooth, suitable for the Schluter 25 installation.	<input type="checkbox"/>
The substrate surface to be flat and smooth with falls to water discharge outlets.	<input type="checkbox"/>
There is no mechanical damage to substrate membrane.	<input type="checkbox"/>
The Schluter 25 installer has read the project specification, viewed the plans and detailed drawings and fully understands the installation substrate requirements.	<input type="checkbox"/>
The Schluter 25 installer has read the Schluter 25 Uncoupling mat product brochure and fully understands the componentry and installation requirements.	<input type="checkbox"/>
The QC Checksheet is available for completion before the Schluter 25 Uncoupling System installation commences (Available from www.waterproofing.co.nz)	
Note: Schluter 25 Uncoupling system is not suitable for membrane systems which have bulky lapping systems.	

WHEN THE SUBSTRATE IS READY, COMPLETE THIS FORM AND EMAIL TO THE WATERPROOFING SUBCONTRACTOR.

Notes			
Name			
Signature		Date	